

Claims

5 1. A guide cart for an implement, comprising:
a frame on which are disposed at least three wheels; and
a first strut and a second strut for effecting mounting of at least
one of said wheels on said frame, wherein said first strut is rotatably
mounted on said frame, and wherein for a mounting of said second
10 strut on said frame at least two spaced-apart mounting points are
provided.

2. A guide cart according to claim 1, wherein said at least
two mounting points are disposed on said second strut.

3. A guide cart according to claim 2, wherein said second
15 strut is in the form of a locking strip having a plurality of mounting
points.

4. A guide cart according to claim 3, wherein said at least
two mounting points are embodied as notches on said locking strip.

5. A guide cart according to claim 4, wherein said notches
20 are open toward a longitudinal side of said locking strip.

6. A guide cart according to claim 4, wherein said notches
cooperate with a locking element that is spring-loaded in a direction
toward a locked position.

7. A guide cart according to claim 3, wherein said locking strip is mounted on a bolt that extends into a slot 16 of said locking strip.

5 8. A guide cart according to claim 7, wherein said locking element is mounted on said frame so as to be rotatable about said bolt.

9. A guide cart according to claim 8, wherein said locking element is disposed on a guide that spans said locking strip and that is mounted on said bolt.

10 10. A guide cart according to claim 9, wherein a rotational movement of said locking element about said bolt is limited by a stop in a direction toward a locked position.

11. A guide cart according to claim 1, wherein said frame is provided with a guide rod on an end of which that faces said wheels is disposed a frame section that extends approximately at right angles to said guide rod, and wherein said first and second struts are mounted on said frame section.

12. A guide cart according to claim 1, wherein said second strut is rotatably mounted on said first strut.

13. A guide cart according to claim 12, wherein said first strut is formed by a plate, wherein one of said wheels is mounted in a first corner of said plate, wherein a second corner of said plate is rotatably mounted on said frame, and wherein said second strut is rotatably mounted in a third corner of said plate.

14. A guide cart according to claim 1, which includes a front wheel and two rear wheels, and wherein said front wheel is held by said first and second struts.